



Technical Datasheet

05-2015

## Knauf Acoustical Sealant

Knauf Acoustical Sealant is white colored, acrylic based sealant which improves sound insulation and acoustical performance when applied in drywall partitions as per Knauf's Technical Datasheet recommendation. It can be used as a general purpose sealant for compatible joints involving gypsum board, metal, concrete, cement, wood plastics. The most common application is sealing the space between the surface and Knauf UW metal tracks in all types of drywall partitions. It can be used with both Knauf EN- BS and ASTM drywall systems.



Sound Insulation



Moisture Resistant



Mold Resistant

Approx. 280 ml

Material code: 461752

## Product Description

Knauf Acoustical Sealant is white colored, acrylic based sealant which improves sound insulation and acoustical performance when applied in drywall partitions as per Knauf's Technical Datasheet recommendation.

It can be used as a general purpose sealant for compatible joints involving gypsum board, metal, concrete, cement, wood plastics. The most common application is sealing the space between the surface and Knauf UW metal tracks in all types of drywall partitions. It can be used with both Knauf EN- BS and ASTM drywall systems.

## Fields of Application

Application surfaces should be clean, dry and free from all contaminants like dust, rust, grease etc.

Cut the nozzle at angle and apply the sealant with a hand or air operated cartridge gun tool immediately to spread the sealant over the surface and give a smooth finish. please refer to the datasheet for further details.

## Properties

- Direct contact of uncured sealant irritates eye and may irritate skin.
- Over exposure to vapor may irritate eyes, nose and throat.
- Avoid eye and skin contact.
- Use with adequate ventilation.
- Do not handle contact lenses with sealant on hands.
- In case of eye contact, flush eyes with water for 15 minutes.
- Obtain medical attention.
- In case of skin contact, remove from skin and flush with water.
- Keep out of reach of children.

## Paintability

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and / or above.

## Clean Up

Excess Caulk should be cleaned off, tools and nonporous surfaces while it is in the uncured state using a wet cloth.

## Users Please Read

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made. The information on this datasheet is subject to change without prior notice.

## Note:

.....

.....

.....

.....

.....

.....

.....

**Please contact our sales department for inquiries about storage and packing.**

<b>Knauf Head Office</b>	<b>Knauf Qatar Branch</b> P.O.Box 27111 Doha, State of Qatar Tel: +974 44528191 Fax: +974 44528181	<b>Knauf Manufacturing Plant</b> P.O.Box 50006 Ras Al Khaimah, U.A.E. Tel: +971 7 221 5300 Fax: +971 7 221 5301	Made in UAE
▶ Phone: +971 4 337 7170			
▶ Fax: +971 4 334 9659			
▶ P.O. Box: 112871, Dubai			
▶ info@knauf.ae	The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of this employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to reply on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, installations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification without notice.		