



Knauf Metal Accessories

03-2017

Knauf Hanger Wire

Galvanized 4,0mm thick steel wires used as suspenders for Knauf D11 Ceiling System. Knauf hanger wires are fixed to the basic ceiling with the help of ceiling dowels and are connected to the metal grid with the help of Knauf Rapid Hangers. Load bearing capacity class = 25 kg.

Product	Weight kg/piece	Packaging unit
Hanger Wire 20 cm	0,020	100
Hanger Wire 40 cm	0,040	100
Hanger Wire 60 cm	0,060	100
Hanger Wire 80 cm	0,080	100
Hanger Wire 100 cm	0,100	100
Hanger Wire 120 cm	0,120	100
Hanger Wire 140 cm	0,140	100

Knauf Head Office

- ▶ Phone: +971 4 337 7170
- ▶ Fax: +971 4 334 9659
- ▶ P.O. Box: 112871, Dubai
- ▶ info@knauf.ae

Knauf Qatar Office

P.O.Box 27111
Doha, State of Qatar
Tel: +974 44528191
Fax: +974 44528181

Knauf Manufacturing Plant

P.O.Box 50006
Ras Al Khaimah, U.A.E.
Tel: +971 7 221 5300
Fax: +971 7 221 5301



The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of this employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to reply on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, installations or buildings to ensure compliance with all regulations, in cluding health and safety regulations. Knauf reserves the right to amend technical specification without notice.