



Knauf Heavy Gypsum Board XTN Screw

Specially designed screws to be used with heavy and dense gypsum boards.
(For example : Pro HD Board)

Knauf Heavy Gypsum Board XTN Screw

Product Features

Specially designed screws to be used with heavy and dense gypsum boards. (For example : Pro HD Board)

Supplied in packs of 1000 screws.

Flat head to facilitate seating and minimize strip out. Finish - Phosphate.

Application/Installation

Guidelines



Use a standard screw gun with a depth-sensitive nose piece. Suggested screw gun specification for optimal performance- 4amps minimum and Install with head flush with board, no need to counter sink.

Over driving may result in failure of the fastener or strip out of the work surface.

Physical Characteristics

Dimensions (mm)		Material No	Pack Details	
Length	Diameter		Items per Pack	Kg (Approx.)
23	3.9	216603	1000	1.9
38	3.9	216606	1000	2.3
55	3.9	216607	1000	3.15

Performance Data

Fire performance

A1 Non-combustable



Technical Data


Product Specification

Gauge: 3.9mm (Approx.)

Head Type: Flat Head

Recess Type: 6.75mm (Approx.) Phillips

Thread Type: Single lead with reverse thread near head



Knauf Application

Knauf Heavy Gypsum Board XTN Screw provide a solid fix into plasterboards with a dense consistency.

High density board to steel, 0.55 - 1mm (Approx.)

Please contact our sales department for inquiries about storage and packing.

Knauf Head Office

▶ Phone: +971 4 337 7170

▶ Fax: +971 4 334 9659

▶ P.O.Box: 112871, Dubai

▶ info.uae@knauf.com

Knauf Manufacturing Plant

P.O.Box 50006

Ras Al Khaimah, U.A.E.

Tel: +971 7 221 5300

Fax: +971 7 221 5301